

# 5. attribute-filter.xml

## 1. Example of a filter to send attributes to sp.example.asia

Please add following filter expression between `<afp:AttributeFilterPolicyGroup>` and `</afp:AttributeFilterPolicyGroup>` in `attribute-filter.xml`.

```
<!-- Release attributes to sp.example.asia -->

<afp:AttributeFilterPolicy id="PolicyforSifulanAsiaSP">
  <afp:PolicyRequirementRule xsi:type="basic:AttributeRequesterString"
    value="https://sp.example.asia/shibboleth" />

  <afp:AttributeRule attributeID="email">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
  <afp:AttributeRule attributeID="commonName">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
  <afp:AttributeRule attributeID="surname">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
  <afp:AttributeRule attributeID="eduPersonAffiliation">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
  <afp:AttributeRule attributeID="eduPersonEntitlement">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
  <afp:AttributeRule attributeID="eduPersonPrincipalName">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
  <afp:AttributeRule attributeID="eduPersonScopedAffiliation">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
  <afp:AttributeRule attributeID="eduPersonTargetedID">
    <afp:PermitValueRule xsi:type="basic:ANY" />
  </afp:AttributeRule>
</afp:AttributeFilterPolicy>
```