

aacli.shが実行できない問題の対処（その2）

StoredIDを用いている場合、mysql-connector-java-5.1.xx-bin.jar等のJDBCドライバーが適切に配置されていないと、下記のエラーになります。
[Shibboleth IdPでStoredIDを利用するための設定方法\(MySQL\)](#)を参照して /opt/shibboleth-idp/lib/ および /usr/java/tomcat/webapps/idp/WEB-INF/lib/ に配置されていることを確認してください。

```
# ./bin/aacli.sh --configDir=conf/ --principal="test001" --requester="https://test-sp1.gakunin.nii.ac.jp/shibboleth-sp"
Exception in thread "main" org.springframework.beans.factory.BeanCreationException: Error creating bean with name 'shibboleth.
AttributeResolver': Invocation of init method failed; nested exception is edu.internet2.middleware.shibboleth.common.service.
ServiceException: Configuration was not loaded for shibboleth.AttributeResolver service, error creating components.
...
Caused by: edu.internet2.middleware.shibboleth.common.service.ServiceException: Configuration was not loaded for shibboleth.
AttributeResolver service, error creating components.
...
Caused by: org.springframework.beans.factory.BeanCreationException: Unable to create relational database connector, JDBC driver can
not be found on the classpath
    at edu.internet2.middleware.shibboleth.common.config.attribute.resolver.dataConnector.
StoredIDDataConnectorBeanDefinitionParser.buildApplicationManagedConnection(StoredIDDataConnectorBeanDefinitionParser.java:169)
...
```